



OKTOPUS® GGA-E-B 8000 oVH



Load lifting attachment for lifting and positioning of construction elements

Scope of application

The load lifting attachment counterweight balancer GGA-B 8000/58/3,0/6,0 oVH fulfills the requirements of DIN EN 13155. With the integrated load hook and together with slings (e.g. ropes, chains, belts etc.) it serves for lifting and positioning construction elements (e.g. those with integrated crane eye) in difficult to access areas (e.g. below eaves, balconies, stages etc.).

Electrically driven counterweights allow balancing the loads.

Description

- electrically driven counterweights operated with cable remote control (optional radio remote control) for balancing loads up to 8,000 kg
- battery-powered energy supply with high capacity
- built-in gauge for monitoring energy supply

WORKING LOAD LIMIT OF THE COUNTERWEIGHT BALANCER

Overhang	Working Load Limit of the counterweight balancer
1,50 m	8,000 kg
1,75 m	6,400 kg
2,00 m	5,250 kg
2,25 m	4,300 kg
2,50 m	3,650 kg
2,75 m	3,000 kg
3,00 m	2,500 kg

APPLICATION DATA

Counterweights	58 pieces removable (1 counterweight = 50 kg)
Operation	cable remote control, radio remote control optional
Power supply	24 V battery system
Weight	approx. 1,200 kg (without counterweights) approx. 4,100 kg (with 34 pieces counterweights)

